
AES <sub>GSM</sub>	Can Gate Prime Ge		CATE PLUS K	
i-GATE	I-GATE-PR	RIME	I-GATE-PLUS	
GSM gate opener with IOS & Android Apps.	AES AE PR AF	0	AES Lite APP	
Numbers for caller ID access.	250		1280	
FOTA – Upgrade firmware via SMS.	$\checkmark$		$\checkmark$	
Trigger, latch and unlatch gates by SMS or with app.	$\checkmark$		$\checkmark$	
Auto call feature to schedule outgoing call (prevents SIM card being deactivated).	$\checkmark$		$\checkmark$	
Activity log feature.	$\checkmark$		$\checkmark$	
Includes 7 day time clock.	$\checkmark$		$\checkmark$	
Check stored numbers by SMS.	$\checkmark$		$\checkmark$	
Volt free momentary relay outputs.	2		1	
Check if gates are opened or closed (limit switch).	$\checkmark$		X	
Check relay status.	$\checkmark$		$\checkmark$	
SMS passcode access for non stored numbers.	$\checkmark$		$\checkmark$	
Store up to four phone numbers to receive SMS alerts each time the unit is used to grant access.	$\checkmark$		$\checkmark$	
Program times for the relay(s) to operate automatically.	$\checkmark$		$\checkmark$	
Push-To-Exit time limits.	$\checkmark$		$\checkmark$	
E-LOOP* Connection Features.	X		$\checkmark$	
SMS Notification when E-loop battery is low (4 Numbers).	X		$\checkmark$	
E-Loop only OR E-Loop & remote lock out times.	X		$\checkmark$	
Suspend times.	×		$\checkmark$	
		DETAILS		
Area code: EU (Europe)	Power	12-24v ac/dc (n		
US (USA) AU (Australia & NZ)	Current Weather Rating	25mA (standby) IP67	. 80mA (when called)	

\*e-Loop sold separately. \* Full app functionality will be released at a later date. Direct SMS commands can be used.



DETAILS		
Power	12-24v ac/dc (not supplied)	
Current	25mA (standby). 80mA (when called)	
Weather Rating	IP67	
Relay Load	24v 2A	
Relay Type	N/C and N/O. Latching & momentary	